



APRON FEEDER (AB38-15/6)



ATEX SUITABLE

General Characteristics

Model	APRON FEEDER AB38-15/6
Construction	Reforce Chassis Steel. L: 5700 - 6200 mm
Width	1400 - 2200mm
Drive Diameter	Ø528mm

Advantages

Belt feeders are designed for the continuous and uniform storage and continuous and uniform storage and dosing of different of different materials. They are especially suitable for solid materials for solid materials, including clays.

Their drive roller is driven by a geared motor with a frequency converter option. frequency converter option. For materials with a high degree of humidity, the equipment is equipped with drums with special drums with a special coating of high adherence ceramic material to ceramic material with high adherence to the belt.

- Variable Production
- Reenforced Structure
- Movement detection
- Liability

Application Sectors

Mining
Recycling
Ceramic
Agri-food industry
Waste Applications
Bulk Materials

CE Normative

This partly completed machine is in compliance with the following relevant provisions of the EC Directives: 2004/108/EC (EMC Directive).

The protection objectives of the Low Voltage Directive 2006/95/EC are in accordance with Annex I, No. 1.5.1 of the EC Machinery Directive 2006/42/EC.

The following standards have also been applied:

EN ISO 12100-1:2003.
 EN ISO 12100-2:2003.
 EN ISO 13857:2008.
 And EN 619:2002.

