



IDLER BELT CONVEYOR (CCAR-15, 20, 35)



ATEX SUITABLE

General Characteristics

Model	CCAR-15, 20, 35°
Construction	Conveyor belt, profile UPN, Idler Stations 15, 20, 35°
Width	300 – 1800 mm
Lenght	2500 – 15000 mm

Advantages

The INGEPROA CCAR Conveyor belt with UPN profile and idler station, provides constant product flow, chassis robustness and minimum maintenance.

Special enclosures and sealing system

- Conveyor belts of different widths
- Adapted to any length and production required.
- Different configurations and designs according to the application.
- Special scraping and cleaning system for drive and under-belt.
- Rotation detector.
- Belt deflection control.
- Reinforced stations.
- Anti-fall protection for lower rollers.

Application Sectors

Mining
Recycling
Agri-food industry
Waste Applications
Bulk Materials
Ceramic

CE Normative

This partly completed machine is in compliance with the following relevant provisions of the EC Directives: 2004/108/EC (EMC Directive).

The protection objectives of the Low Voltage Directive 2006/95/EC are in accordance with Annex I, No. 1.5.1 of the EC Machinery Directive 2006/42/EC.

The following standards have also been applied:

EN ISO 12100-1:2003.
 EN ISO 12100-2:2003.
 EN ISO 13857:2008.
 And EN 619:2002.

