



## CHAIN CONVEYOR (DL-37-K)



### General Characteristics

<b>Model</b>	CHAIN CONVEYOR DL-37-K
<b>Construction</b>	Reinforced chassis Carbon Steel.
<b>Width</b>	1700 - 2200mm
<b>Lenght</b>	6300 – 7300mm

### Advantages

The INGEPROA DL-37-K chain conveyor, is designed for continuous and uniform storage and dosing of different types of solid materials. Possibilities with different combination, 0°-45-0°, 0°-30°-15°...

The combination of high-quality mechanical elements and its robust design allow it to absorb strong impacts derived from the discharges of its feeding.

Its power and sealing prevent spillage and allow dosing of high tonnages from the feed hopper, even with materials with a high degree of humidity.

- Removable front
- central chain lubrication system
- planetary reducer
- safety in chain tensioning.

### Application Sectors

**Mining**  
**Recycling**  
**Agri-food industry**  
**Waste Applications**  
**Bulk Materials**  
**Automotive**

### CE Normative

This partly completed machine is in compliance with the following relevant provisions of the EC Directives: 2004/108/EC (EMC Directive).

The protection objectives of the Low Voltage Directive 2006/95/EC are in accordance with Annex I, No. 1.5.1 of the EC Machinery Directive 2006/42/EC.

The following standards have also been applied:

EN ISO 12100-1:2003.  
 EN ISO 12100-2:2003.  
 EN ISO 13857:2008.  
 And EN 619:2002.

